



Solid prefinished parquet

Solid parquet has all advantages of wooden flooring. Wood is one of the oldest and most appreciated material, used for the flooring. It has distinctive, unique natural structure and colour. Solid parquet is an investment for several generations. Its thickness allows it to be renewed (sanded) several times. Boards are of different dimensions. Lengths range from 400 mm to 1500 mm, widths from 82 mm to 150 mm and thicknesses from 15 mm to 20 mm. Solid parquet has to be fully glued to the surface. All parquets are already sanded and varnished or oiled. Some of them have also additional treatments, such as brushing, handscraping, etc. Varnishes and oils are hardened with UV rays. The bevelled edges of the planks additionally emphasize distinctive wood structure.

Advantages:

- warm,
- antistatic,
- suitable from ecological point of view,
- with oiled surface, parquet can regulate the moisture in the room

Tehnickal data:

plank dimension	differenet
underfloor heating	unsuitable
installation	fully glued on the surface
durability	renewable

tongue + groove installation system






OAK A



OAK ABCD



OAK ABCD,
LIGHT SMOKED, OILED



OAK BRUSHED, BLACK
EDGE AND GRAINS



OAK BRUSHED, 002



OAK BRUSHED, 003 COGNAC




OAK ABC BRUSHED,
WHITE WASHED, STIL 1



OAK A, BRUSHED,
WHITE WASHED, STIL 2



OAK ABCD, GUNSTOCK



OAK ABCD, CRIMSON



OAK ABCD, HAND SCRAPED,
031



OAK CD, HAND SCRAPED,
COFFE




alpod



IPE



TIGERWOOD



TEAK




CABREUVA



JATOBA



MERBAU




PYNKADO



KEMPAS



CUMARU



BLACK SIRIS




ZEBRANO




ASH



WALNUT AFRICAN



CHESTNUT




DOUSSIE




IROKO



BLACK BIRCH



PALISANDER




BALSAMO



MAPLE



WALNUT AMERICAN, BRUSHED



WALNUT AMERICAN



MAPLE CANADIAN



CHERRY AMERICAN